NSN 5962-01-161-3507

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-161-3507

Body Length:	
0.840 inches	
Body Width:	
Between 0.220 inches and	l 0.310 inches
Body Height:	
Between 0.140 inches and	I 0.185 inches
Maximum Power Dissipa	tion Rating:
739.0 milliwatts	
Operating Tempurature	Range:
-55.0/+125.0 degrees cels	ius
Storage Tempurature Ra	nge:
-65.0/+150.0 degrees cels	ius
End Application:	
Radar system, type an/fps	-117
Features Provided:	
Hermetically sealed and m	nonolithic and high impedance and 3-state output and programmable and bipolar
Inclosure Material:	
Ceramic and glass	
Inclosure Configuration:	
Dual-in-line	
Output Logic Form:	
Transistor-transistor logic	
Input Circuit Pattern:	
10 input	
Case Outline Source And	d Designator:
D-2 mil-m-38510	
Terminal Surface Treatm	ent:
Solder	
Voltage Rating And Type	Per Characteristic:
5.5 volts power source	
Time Rating Per Chacter	istic:
75.00 nanoseconds propa	agation delay time, low to high level output and 75.00 nanoseconds propagation delay time, high to low level
output	
Memory Device Type:	
Rom	
Memory Capacity:	
Unknown	
Terminal Type And Quan	itity:
16 printed circuit	
Shelf Life:	
N/a	
Unit Of Measure:	

NSN 5962-01-161-3507

Memory Microcircuit - Page 2 of 2

Demilitarization:

Yes - demil/mli

Fiig:

A458a0

