NSN 5962-01-161-3511

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-161-3511 **Body Length:** 1.290 inches **Body Width:** Between 0.500 inches and 0.610 inches **Body Height:** Between 0.150 inches and 0.210 inches **Maximum Power Dissipation Rating:** 1.02 watts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** Radar system, type an/fps-117 **Features Provided:** Hermetically sealed and monolithic and bipolar and high impedance and schottky and programmable **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 14 input **Case Outline Source And Designator:** D-3 mil-m-38510 **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 5.5 volts power source **Time Rating Per Chacteristic:** 100.00 nanoseconds propagation delay time, low to high level output and 100.00 nanoseconds propagation delay time, high to low level output **Memory Device Type:** Rom **Memory Capacity:** Unknown **Terminal Type And Quantity:** 24 printed circuit

N/a

Shelf Life:

Unit Of Measure:

NSN 5962-01-161-3511

Memory Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0