NSN 5962-01-161-3512

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-161-3512

| Body Length: |
|--|
| 1.290 inches |
| Body Width: |
| Between 0.500 inches and 0.610 inches |
| Body Height: |
| Between 0.150 inches and 0.210 inches |
| Maximum Power Dissipation Rating: |
| 1.02 watts |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| End Application: |
| Radar system, type an/fps-117 |
| Features Provided: |
| Hermetically sealed and monolithic and bipolar and high impedance and schottky and programmable |
| Inclosure Material: |
| Ceramic and glass |
| Inclosure Configuration: |
| Dual-in-line |
| Output Logic Form: |
| Transistor-transistor logic |
| Input Circuit Pattern: |
| 14 input |
| Case Outline Source And Designator: |
| D-3 mil-m-38510 |
| Terminal Surface Treatment: |
| Solder |
| Voltage Rating And Type Per Characteristic: |
| 5.5 volts power source |
| Time Rating Per Chacteristic: |
| 100.00 nanoseconds propagation delay time, low to high level output and 100.00 nanoseconds propagation delay time, high to low level |
| output |
| Memory Device Type: |
| Rom |
| Memory Capacity: |
| Unknown |
| Terminal Type And Quantity: |
| 24 printed circuit |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

NSN 5962-01-161-3512

Memory Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0