NSN 5962-01-161-4550

Digital Microcircuit - Page 1 of 1

A458a0



View Online at https://aerobasegroup.com/nsn/5962-01-161-4550

view Offilite at https://aerobasegroup.com/hist//0302-01-101-4000
Body Length:
0.440 inches
Body Width:
Between 0.245 inches and 0.285 inches
Body Height:
Between 0.045 inches and 0.085 inches
Maximum Power Dissipation Rating:
198.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and low power and schottky and w/clock and w/inhibit
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Flat pack
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
12 input
Design Function And Quantity:
1 shift register, parallel load
Case Outline Source And Designator:
F-5 mil-m-38510
Time Rating Per Chacteristic:
58.00 nanoseconds propagation delay time, low to high level output and 58.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-m-38510/306 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig: