

View Online at <https://aerobasegroup.com/nsn/5962-01-162-4272>

**Body Length:**

0.785 inches

**Body Width:**

Between 0.220 inches and 0.310 inches

**Body Height:**

0.185 inches

**Maximum Power Dissipation Rating:**

500.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**Features Provided:**

Hermetically sealed and monolithic and electrostatic sensitive

**Inclosure Material:**

Ceramic

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Complementary-metal oxide-semiconductor logic

**Input Circuit Pattern:**

Triple 3 input

**Design Function And Quantity:**

3 gate, nand

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

18.5 volts power source

**Time Rating Per Characteristic:**

250.00 nanoseconds propagation delay time, low to high level output and 250.00 nanoseconds propagation delay time, high to low level output

**Test Data Document:**

51215-ve477-5052 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

14 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0