# NSN 5962-01-162-4571

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-162-4571

## Body Length:

0.840 inches

#### Body Width:

Between 0.220 inches and 0.310 inches

#### **Body Height:**

0.185 inches

#### **Maximum Power Dissipation Rating:**

500.0 milliwatts

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### **Features Provided:**

Hermetically sealed and burn in and monolithic and positive outputs

#### Inclosure Material:

Ceramic

#### Inclosure Configuration:

Dual-in-line

#### Input Circuit Pattern:

Quad 1 input

### **Design Function And Quantity:**

4 switch, analog, single pole single throw normally open

### Case Outline Source And Designator:

D-2 mil-m-38510

### **Terminal Surface Treatment:**

Tin

### Time Rating Per Chacteristic:

750.00 nanoseconds propagation delay time, low to high level output and 1000.00 nanoseconds propagation delay time, high to low level output

#### Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

#### Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

Yes - demil/mli

#### Fiig:

A458a0