NSN 5962-01-162-5863

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-162-5863

Body Outside Diameter:
Between 0.335 inches and 0.370 inches
Body Height:
Between 0.165 inches and 0.185 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Receiving set, countermeasures, type an/wlr-8
Features Provided:
Hermetically sealed and monolithic and low drift and low current and low noise
Inclosure Material:
Metal
Inclosure Configuration:
Can
Input Circuit Pattern:
2 input
Design Function And Quantity:
1 amplifier, operational, general purpose
Case Outline Source And Designator:
A-1 mil-m-38510
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
20.0 volts power source
Test Data Document:
05869-725004-356 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
8 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A458a0