NSN 5962-01-163-2757



Digital Microcircuit - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5962-01-163-2757 **Body Length:** 0.400 inches **Body Width:** Between 0.245 inches and 0.255 inches **Body Height:** Between 0.125 inches and 0.135 inches **Maximum Power Dissipation Rating:** 800.0 milliwatts **Operating Tempurature Range:** -0.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and monolithic and positive outputs **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** Dual 2 input **Design Function And Quantity:** 2 driver, power **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** 5.5 volts power source **Time Rating Per Chacteristic:** 110.00 nanoseconds propagation delay time, low to high level output and 110.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 55006-1264-546 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 8 printed circuit Shelf Life: N/a **Unit Of Measure:**

Fiig: A458a0

Demilitarization: Yes - demil/mli