

View Online at https://aerobasegroup.com/nsn/5662-01-163-4201 Body Length: 4.020 inches Body Widht: 2.000 inches Body Hight: 0.420 inches Operating Tempurature Range: -40.0 to 90.0 degrees celsius Storage Tempurature Range: -55.0 to 125.0 degrees celsius Features Provided: Bipolar and wipdoar and widdock Inclosure Material: Plastic Inclosure Material: Plastic Inclosure Configuration: Dual-Indine Output Logic Form: Transistor-transistor logic Input Circuit Patern: 11 input Design Function And Quantity: 1 coveret, analog to digital Terminal surfaces gold Procisus Material: Rodiz Storage Instruction And Quantity: 1 coveret, analog to digital Terminal surfaces gold Procisus Material Coid Test Data Document: 8257-pa60341 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacture drawing, etc; excluss ants	NSN 5962-01-163-4201 Digital-linear Microcircuit - Page 1 of 1	AeroBase Group
420 indust 2420 indust 2420 indust 2420 indust 2420 indust 0420 indust 0400 degrees celsius 0400 degrees celsius 04000 degrees celsius 04000 degrees celsius 1 1 04000 degrees celsius 1 1 1 04000 degrees celsius 1 1 1 1 1 1 1 1 1	View Online at https://aerobasegroup.com/nsn/5962-01-163-4201	
Body Width: 2020 inches 2040 inches Color bes	Body Length:	
2.020 indes 6x0y Height: 0.102 in obes 0.202 in obes 2.402 in obes 2.503 in 28.0 obegrees celsius 2.504 in 28.0 obegrees celsius 2.504 in obes Bioplar and wiclock Incloure Material: Plastic 1.504 in obes Outplic form: 1.504 in obes 1.504 in ob	4.020 inches	
Body Height: 0.420 inches Persting Tempurature Range: -0.010 90.0 degrees celsius Storage Tempurature Range: -5.010 125.0 degrees celsius Fatures Provided: Paterse Provided: Paterse Trovided: Paterse Transfort Degic Transfort Transfort Degic Paterse Transfort Degic	Body Width:	
0420 indes 0420 indegress colsius 0400 dogress colsius 0400 dogress colsius 0400 indegress colsius <td>2.020 inches</td> <td></td>	2.020 inches	
Gerating Tempurature Range: 4:0.0 to 90.0 degrees celsius Sociage Tempurature Range: 5:5.0 to 125.0 degrees celsius Fotures Provided: Bipolar and unipolar and wickock Inclosure Material: Packers Provided: Dual-inline Outlogic Form: Tansistor-transistor logic Indicuster Material: Positor Tansistor-transistor logic Input Croutit Pattern: 1 input Design Function And Quantity: 1 converter, analog to digital Pericus Material And Location: 1 converters, analog to digital Procisus Material And Location: 1 converter 10:0 valarces gold Procisus Material And Location: 1 converter 10:0 valarces gold Procisus Material And Location: 1 converter 1 coludes any specification, standard or other document that may be referenced in a basic governing drawing, etci, a specification, standard or other document that may be referenced in a basic governing drawing, trais is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etci, a prived irccutit 1 converter 1 converter	Body Height:	
400 to 90.0 degrees celsius 5Xor 25.0 degrees celsius Fatures Provided: Bipdar and wickock Inclosure Material: Plastic Polation: Dialphiline Output Logic Form: Transistor-transistor logic Input Crucit Pattern: 1 linput Design Function And Quantity: 1 converter, analog to digital Converter, analog to digital Volts power source Precious Material: 1 Source Source Precious Material And Location: 1 Source source Precious Material And Location: 1 Calcus and unity (bis is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etcles 1 Source source Precious Material Inducation: 1 calcus any specification, standard or other document that may be referenced in a basic governing drawing; 1 calcus any specification, standard or other document that may be referenced in a basic governing drawing; 1 calcus any specification, standard or other document that may be referenced in a basic governing drawing; 1 calcus any specification, standard or other document that may be referenced in a basic governing drawing) 1 calcus	0.420 inches	
Storage Temperature Range: 55.0 to 125.0 degrees celsius Features Provided: Bipolar and unipolar and welcock Inclosure Material: Plastic Inclosure Configuration: Dual-in-line Output Logic Form: Transistor-transistor logic Input Dosign Function And Quantity: 1 converte, analog to digital Terninal Surface Treatment: Gold Voltage Rating And Type Per Characteristic: 18.0 volts power source Precious Material: Gold Precious Material: Gold Frectous Material And Location: Tarminal surfaces gold Frectous Material: Gold Frectous Material: Gold Frectous Material: Gold Frectous Material: Rocius and problement: Gold Frectous Material: Rocius and problement: Rocius and problement: Rocius and problement: Rocius and problement: Rocius and problement: <td>Operating Tempurature Range:</td> <td></td>	Operating Tempurature Range:	
- 56.0 to 125.0 degrees celsius Fatures Provide: - Fatures Provide: - Biolar and unipolar and wichock - Inclosure Material: - Plastic - Inclosure Configuration: - Dual-inline - Dual-instor-transistor logic - Transistor-transistor logic - Input Circuit Pattern: - 1 Input - Design Function And Quantity: - 1 converter, analog to digital - Periorus Material: - Roles Material: - Roles Material: - Roles Material: - Gold - Process Material: - Gold - Factoration: - Gold - Factoration: - Gold - Process Material: - Gold - Factoration:	-40.0 to 90.0 degrees celsius	
Features Provide: Bipolar and unipolar and w/clock Inclosure Material: Plastic Inclosure Configuration: Dual-in-line Output Logic Form: Transistor-transistor logic Input Circuit Pattern: 11 input Design Function And Quantity: 1 converter, analog to digital Terminal Surface Treatment: Gold Voltage Rating And Type Per Characteristic: 18.0 volts power source Precious Material: Gold Factorial Surface Gold Terminal surfaces gold Precious Material: Cold Terminal surface sold Precious Material: Cold Terminal surfaces gold Precious Material: Cold Test Data Document: Coldses any specification, standard or other document that may be referenced in a basic governing drawing, etc.: Tariant Type And Quantity: Tariant Type And Quantity: Tariant Circuit Nate	Storage Tempurature Range:	
Biplar and unipolar and wolock. Inclosure Material: Plastic Inclosure Configuration: Dualt-line Output Logic Form: Transistor-transistor logic Intercent Patterne: 11 input Posign Function And Quantity: 1 converter, analog to digital Forminal Surface Treatment: Gold Values Rating And Type Per Characteristic: 18.0 volts power source Precious Material: Gold Istribution and Location: Terminal surfaces gold Precious Material: Gold Forbat Document: Kedues any specification, standard or other document that may be referenced in a basic governing drawing, etc.; Kedues any specification, standard or other document that may be referenced in a basic governing drawing, etc.; Torpited circuit Na	-55.0 to 125.0 degrees celsius	
Inclosure Material: Plastic Inclosure Configuration: Dual-in-line Output Logic Form: Transistor-transistor logic Input Treut Pattern: 11 input Design Function And Quantity: 1 converter, analog to digital Terminal Surface Treatment: Gold Precious Material: 18.0 volts power source Precious Material: Gold Startial Surfaces gold Precious Material: 60/d Terminal surfaces gold Precious Material: 60/d Test Data Document: 62577-pa60341 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: 6210 cuput: 72 printed circuit 72 printed circuit N/a	Features Provided:	
Plastic Iclosure Configuration: Dual-in-line Output Logic Form: Transistor-transistor logic Input Circuit Pattern: 11 input Design Function And Quantity: 1 converter, analog to digital Terminal Surface Treatment: Gold Valge Rating And Type Per Characteristic: 18.0 volts power source Procious Material And Location: Terminal surfaces gold Procious Material: Bodd Story TrapeG0341 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; sculues any specification, standard or other document that may be referenced in a basic governing drawing; etc.; reminal Type And Quantity: 12 printed circuit Na	Bipolar and unipolar and w/clock	
Inclosure Configuration: Dual-in-line Output Logic Form: Transistor-transistor logic Input Circuit Pattern: 11 input Design Function And Quantity: 1 converter, analog to digital Terminal Surface Treatment: Gold Value Rating And Type Per Characteristic: 18.0 volts power source Precious Material And Location: Terminal surfaces gold Precious Material: 6old Sold Precious Material: 82577-pa60341 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing; etc.; 72 printed circuit Na	Inclosure Material:	
Dual-in-line Output Logic Form: Transistor-transistor logic Input Circuit Pattern: 11 input Design Function And Quantity: 1 converter, analog to digital Terminal Surface Treatment: Gold Voltage Rating And Type Per Characteristic: 18.0 volts power source Precious Material And Location: Terminal surfaces gold Precious Material: Gold S2577-pa60341 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; reminal Type And Quantity: 72 printed circuit Sheff Life: Na	Plastic	
Putput Logic Form: Transistor-transistor logic Injut Postign Function And Quantity: 1 converter, analog to digital Perminal Surface Treatment: Gold Voltage Rating And Type Per Characteristic: 18.0 volts power source Precious Material And Location: Terminal surfaces gold Precious Material: Gold Stort Data Document: Restronce and y specification, standard or other document that may be referenced in a basic governing drawing, etc.; Restronce any specification, standard or other document that may be referenced in a basic governing drawing, etc.; Priminal Type And Quantity: 12.0 printed circuit Main Na	Inclosure Configuration:	
Transistor transistor logic Input Circuit Pattern: 11 input Design Function And Quantity: 1 converter, analog to digital Terminal Surface Treatment: Gold Voltage Rating And Type Per Characteristic: 18.0 volts power source Precious Material And Location: Terminal surfaces gold Precious Material: Gold S2577-pa60341 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; Terminal Type And Quantity: 72 printed circuit Sheff Life: Na	Dual-in-line	
Input Circuit Pattern: 11 input Design Function And Quantity: 1 converter, analog to digital Terminal Surface Treatment: Gold Voltage Rating And Type Per Characteristic: 18.0 volts power source Precious Material And Location: Terminal surfaces gold Precious Material: Gold S2577-pa60341 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 72 printed circuit Sheff Life: N/a	Output Logic Form:	
11 input Design Function And Quantity: 1 converter, analog to digital Terminal Surface Treatment: Gold Voltage Rating And Type Per Characteristic: 18.0 volts power source Precious Material And Location: Terminal surfaces gold Precious Material: Gold Sold Precious Material: Gold Terminal surfaces gold Precious Material: Gold Test Data Document: 82577-pa60341 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing. Terminal Type And Quantity: 72 printed circuit Sheff Life: Na	Transistor-transistor logic	
Period Previous Automative Converter, analog to digital Terminal Surface Treatment: Gold Voltage Rating And Type Per Characteristic: 18.0 volts power source Precious Material And Location: Terminal surfaces gold Precious Material: Gold Sold Precious Material: Gold Precious Material: Gold Terminal surfaces gold Precious Material: Gold Sold Precious Material: Cold Terminal surface gold Precious Material: Gold Terminal Type And Quantity: rectious any specification, standard or other document that may be referenced in a basic governing drawing, etc.: reprinted circuit Sheff Life: N/a	Input Circuit Pattern:	
1 converter, analog to digital Ferminal Surface Treatment: Gold Voltage Rating And Type Per Characteristic: 18.0 volts power source Precious Material And Location: Terminal surfaces gold Precious Material: Gold Precious Material: Gold Precious Material: Gold Precious Material: Gold Test Data Document: 82577-pa60341 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 72 printed circuit Shelf Life: N/a	11 input	
Terminal Surface Treatment: Gold Voltage Rating And Type Per Characteristic: 18.0 volts power source Precious Material And Location: Terminal surfaces gold Precious Material: Gold Yest Data Document: 82577-pa60341 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 72 printed circuit Shelf Life: N/a	Design Function And Quantity:	
Gold Voltage Rating And Type Per Characteristic: 18.0 volts power source Precious Material And Location: Terminal surfaces gold Precious Material: Gold Precious Material: Bold Precious Material: Gold Precious Material: Gold Fest Data Document: 82577-pa60341 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing); Terminal Type And Quantity: 72 printed circuit Sheff Life: N/a	1 converter, analog to digital	
 Voltage Rating And Type Per Characteristic: 18.0 volts power source Precious Material And Location: Terninal surfaces gold Precious Material: Gold Test Data Document: 82577-pa60341 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; preciudes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 72 printed circuit Shelf Life: N/a 	Terminal Surface Treatment:	
 18.0 volts power source Precious Material And Location: Terminal surfaces gold Precious Material: Gold Test Data Document: 82577-pa60341 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 72 printed circuit Shelf Life: N/a 	Gold	
Precious Material And Location:Terminal surfaces goldPrecious Material:GoldTest Data Document:82577-pa60341 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;excludes any specification, standard or other document that may be referenced in a basic governing drawing)Terminal Type And Quantity:72 printed circuitShelf Life:N/a	Voltage Rating And Type Per Characteristic:	
Terminal surfaces goldPrecious Material:GoldTest Data Document:82577-pa60341 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;excludes any specification, standard or other document that may be referenced in a basic governing drawing)Terminal Type And Quantity:72 printed circuitShelf Life:N/a	18.0 volts power source	
Precious Material: Gold Test Data Document: 82577-pa60341 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 72 printed circuit Shelf Life: N/a	Precious Material And Location:	
Gold Test Data Document: 82577-pa60341 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 72 printed circuit Shelf Life: N/a	Terminal surfaces gold	
Test Data Document: 82577-pa60341 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 72 printed circuit Shelf Life: N/a	Precious Material:	
 82577-pa60341 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 72 printed circuit Shelf Life: N/a 	Gold	
excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 72 printed circuit Shelf Life: N/a	Test Data Document:	
Terminal Type And Quantity: 72 printed circuit Shelf Life: N/a	82577-pa60341 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment r	manufacturer drawing, etc.;
72 printed circuit Shelf Life: N/a	excludes any specification, standard or other document that may be referenced in a basic governing drawing)	
Shelf Life: N/a	Terminal Type And Quantity:	
N/a	72 printed circuit	
	Shelf Life:	
Unit Of Measure:	N/a	
	Unit Of Measure:	

Fiig: A458a0

Demilitarization: Yes - demil/mli