## NSN 5962-01-163-9174

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-163-9174

## **Body Length:** 0.840 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** 0.185 inches **Maximum Power Dissipation Rating:** 424.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+165.0 degrees celsius **End Application:** 1270-01-132-2437 antenna, radar **Features Provided:** Hermetically sealed and burn in and low power and schottky and monolithic and w/enable **Inclosure Material:** Ceramic Inclosure Configuration: Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 10 input **Design Function And Quantity:** 4 receiver, line **Case Outline Source And Designator:** D-2 mil-m-38510 **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 7.0 volts power source **Test Data Document:** 97942-584r482 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 16 printed circuit Shelf Life: N/a Unit Of Measure:

---

- **Demilitarization:**
- Yes demil/mli

## NSN 5962-01-163-9174

Digital Microcircuit - Page 2 of 2

**Fiig:** A458a0

