## NSN 5962-01-163-9216

Digital Microcircuit - Page 1 of 1

A458a0



View Online at https://aerobasegroup.com/nsn/5962-01-163-9216

Body Length:
Between 0.755 inches and 0.785 inches
Body Width:
Between 0.245 inches and 0.271 inches
Body Height:
0.180 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Radio-telemetric data set an/srq-4
Features Provided:
Hermetically sealed and high speed and w/totem pole output and asynchronous and complementary outputs
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Emitter-coupled logic
Input Circuit Pattern:
4 input
Design Function And Quantity:
1 prescaler
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-5.2 volts power source
Time Rating Per Chacteristic:
14.00 nanoseconds propagation delay time, low to high level output and 14.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
16 printed circuit
Shelf Life:
N/a
Unit Of Measure:
<del>-</del>
Demilitarization:
Yes - demil/mli
Fiia: