NSN 5962-01-164-5092

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-164-5092

Body Length: 0.785 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** 0.185 inches **Maximum Power Dissipation Rating:** 200.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+175.0 degrees celsius **Features Provided:** Monolithic **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Input Circuit Pattern:** Quad 2 input **Design Function And Quantity:** 4 gate, nor **Case Outline Source And Designator:** D-1 mil-m-38510 **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 18.0 volts power source **Test Data Document:** 81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 14 printed circuit **Specification Data:** 81349-mil-m-38510/52 government specification Shelf Life: N/a Unit Of Measure: **Demilitarization:** Yes - demil/mli

NSN 5962-01-164-5092

Digital Microcircuit - Page 2 of 2

Fiig: A458a0

