Linear Microcircuit - Page 1 of 1

View Online at https://aerobasegroup.com/nsn/5962-01-164-5280



## **Body Outside Diameter:**

0.370 inches

#### **Body Height:**

0.185 inches

## **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

### **Storage Tempurature Range:**

-65.0/+150.0 degrees celsius

### **End Application:**

Test set, countermeasures an/usm-464

## **Features Provided:**

Hermetically sealed and monolithic and fast settling and wideband and frequency compensated

### **Inclosure Material:**

Metal

### **Inclosure Configuration:**

# Can

**Input Circuit Pattern:** 

2 input

## **Design Function And Quantity:**

1 amplifier, operational, general purpose

# **Terminal Surface Treatment:**

Solder

## Voltage Rating And Type Per Characteristic:

20.0 volts power source

## **Test Data Document:**

94117-321051 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

## **Terminal Type And Quantity:**

8 pin

## Shelf Life:

N/a

# Unit Of Measure:

--

#### **Demilitarization:**

Yes - demil/mli

#### Fiig:

A458a0