NSN 5962-01-164-8741

Linear Microcircuit - Page 1 of 1



Body Length:
Between 0.755 inches and 0.785 inches
Body Width:
Between 0.245 inches and 0.286 inches
Body Height:
Between 0.145 inches and 0.169 inches
Maximum Power Dissipation Rating:
650.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
5840-01-141-4378 radar set
Features Provided:
High performance and high slew rate and hermetically sealed and low power
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
Input Circuit Pattern:
Input Circuit Pattern: Quad 2 input
Input Circuit Pattern: Quad 2 input Design Function And Quantity:
Input Circuit Pattern: Quad 2 input Design Function And Quantity: 4 amplifier, operational, general purpose
Input Circuit Pattern: Quad 2 input Design Function And Quantity: 4 amplifier, operational, general purpose Terminal Surface Treatment:
Input Circuit Pattern: Quad 2 input Design Function And Quantity: 4 amplifier, operational, general purpose Terminal Surface Treatment: Solder
Input Circuit Pattern: Quad 2 input Design Function And Quantity: 4 amplifier, operational, general purpose Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic:
Input Circuit Pattern: Quad 2 input Design Function And Quantity: 4 amplifier, operational, general purpose Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 36.0 volts power source
Input Circuit Pattern: Quad 2 input Design Function And Quantity: 4 amplifier, operational, general purpose Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 36.0 volts power source Terminal Type And Quantity:
Input Circuit Pattern: Quad 2 input Design Function And Quantity: 4 amplifier, operational, general purpose Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 36.0 volts power source Terminal Type And Quantity: 14 printed circuit
Input Circuit Pattern: Quad 2 input Design Function And Quantity: 4 amplifier, operational, general purpose Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 36.0 volts power source Terminal Type And Quantity: 14 printed circuit Shelf Life:
Input Circuit Pattern: Quad 2 input Design Function And Quantity: 4 amplifier, operational, general purpose Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 36.0 volts power source Terminal Type And Quantity: 14 printed circuit Shelf Life: N/a
Input Circuit Pattern: Quad 2 input Design Function And Quantity: 4 amplifier, operational, general purpose Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 36.0 volts power source Terminal Type And Quantity: 14 printed circuit Shelf Life: N/a
Input Circuit Pattern: Quad 2 input Design Function And Quantity: 4 amplifier, operational, general purpose Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 36.0 volts power source Terminal Type And Quantity: 14 printed circuit Shelf Life: N/a Unit Of Measure:

A458a0