## NSN 5962-01-165-0869

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-165-0869 **Body Length:** 0.985 inches **Body Width:** 0.280 inches **Body Height:** 0.160 inches **Maximum Power Dissipation Rating:** 500.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** 5865-01-096-4994 radar simulator **Features Provided:** Monolithic and high speed and 3-state output **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Input Circuit Pattern:** 10 input **Design Function And Quantity:** 8 buffer and 8 driver, line **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** 18.3 volts power source **Time Rating Per Chacteristic:** 110.00 nanoseconds propagation delay time, low to high level output and 110.00 nanoseconds propagation delay time, high to low level output **Terminal Type And Quantity:** 20 printed circuit Shelf Life: N/a **Unit Of Measure:** 

Fiig:

A458a0

**Demilitarization:** Yes - demil/mli