

View Online at <https://aerobasegroup.com/nsn/5962-01-165-5439>

Body Length:

0.785 inches

Body Width:

0.280 inches

Body Height:

0.180 inches

Maximum Power Dissipation Rating:

200.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and burn in

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Input Circuit Pattern:

14 stage

Design Function And Quantity:

1 counter, binary, ripple carry

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

15.0 volts power source

Time Rating Per Characteristic:

400.00 nanoseconds propagation delay time, low to high level output and 400.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

07690-438271 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

16 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0