NSN 5962-01-165-5440

Digital Microcircuit - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5962-01-165-5440

| Body Length: | |
|-----------------------|--|
| 0.390 inches | |
| Body Width: | |
| Between 0.235 inc | hes and 0.260 inches |
| Body Height: | |
| Between 0.045 inc | hes and 0.085 inches |
| Maximum Power | Dissipation Rating: |
| 143.0 milliwatts | |
| Operating Tempu | rature Range: |
| -55.0/+125.0 degre | es celsius |
| Storage Tempura | ture Range: |
| -65.0/+150.0 degre | es celsius |
| Features Provide | d: |
| Hermetically seale | d and monolithic and low power and schottky |
| Inclosure Materia | I: |
| Ceramic and glass | · |
| Inclosure Configu | Jration: |
| Flat pack | |
| Output Logic For | m: |
| Transistor-transisto | or logic |
| Input Circuit Patte | ern: |
| Dual 2 input | |
| Design Function | And Quantity: |
| 2 counter, binary | |
| Case Outline Sou | rce And Designator: |
| F-2 mil-m-38510 | |
| Terminal Surface | Treatment: |
| Solder | |
| Voltage Rating Ar | nd Type Per Characteristic: |
| 5.5 volts power so | urce |
| Test Data Docum | ent: |
| 81349-mil-m-3851 | 0 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes of | commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and | performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Terminal Type An | Id Quantity: |
| 14 flat leads | |
| Specification Data | a: |
| 81349-mil-m-3851 | 0/327 government specification |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| Demilitarization: | |
| Yes - demil/mli | |

NSN 5962-01-165-5440

Digital Microcircuit - Page 2 of 2

Fiig: A458a0

