## NSN 5962-01-166-3013

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-166-3013

View Online at https://aerobasegroup.com/nsn/5962-01-166-3013
Body Length:
Between 3.168 inches and 3.232 inches
Body Width:
Between 0.880 inches and 0.900 inches
Body Height:
0.205 inches
Maximum Power Dissipation Rating:
750.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
2350-01-089-1261 air defense gun
Features Provided:
Bipolar and hermetically sealed and electrostatic sensitive
Inclosure Material:
Ceramic or glass or metal
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
29 input
Design Function And Quantity:
1 microprocessor
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
5.5 volts power source
Time Rating Per Chacteristic:
200.00 nanoseconds propagation delay time, low to high level output
Test Data Document:
19200-12616490 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
64 printed circuit
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

Yes - demil/mli

## NSN 5962-01-166-3013

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0