## NSN 5962-01-167-5268

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-167-5268

## **Body Length:** 1.290 inches **Body Width:** Between 0.500 inches and 0.610 inches **Body Height:** Between 0.150 inches and 0.210 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** 4933-01-083-0540 test set, rocket **Features Provided:** Hermetically sealed and monolithic and w/strobe **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 6 input **Design Function And Quantity:** 1 decoder, four to sixteen line **Case Outline Source And Designator:** D-3 mil-m-38510 **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 5.5 volts power source **Time Rating Per Chacteristic:** 36.00 nanoseconds propagation delay time, low to high level output and 33.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 19203-9324581 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 24 printed circuit Shelf Life: N/a Unit Of Measure:

**Demilitarization:** 

Yes - demil/mli

## NSN 5962-01-167-5268

Digital Microcircuit - Page 2 of 2

**Fiig:** A458a0

