## NSN 5962-01-167-7163



Digital Microcircuit - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5962-01-167-7163 **Body Length:** 0.410 inches **Body Width:** 0.410 inches **Body Height:** Between 0.045 inches and 0.080 inches **Maximum Power Dissipation Rating:** 800.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Burn in and monolithic **Inclosure Material:** Ceramic **Inclosure Configuration:** Flat pack **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 21 input **Design Function And Quantity:** 1 control **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** -0.5 volts power source and 7.0 volts power source **Time Rating Per Chacteristic:** 60.00 nanoseconds propagation delay time, low to high level output and 60.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 82577-h990021 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 28 flat leads Shelf Life: N/a **Unit Of Measure:** 

Fiig: A458a0

**Demilitarization:** Yes - demil/mli