## NSN 5962-01-168-0829

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-168-0829 **Body Length:** 0.440 inches **Body Width:** Between 0.245 inches and 0.285 inches **Body Height:** Between 0.045 inches and 0.085 inches **Maximum Power Dissipation Rating:** 190.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and burn in and w/preset and w/clear and monolithic **Inclosure Material:** Ceramic **Inclosure Configuration:** Flat pack **Output Logic Form: Emitter-coupled logic Input Circuit Pattern:** 9 input **Design Function And Quantity:** 2 flip-flop, d-type **Case Outline Source And Designator:** F-5 mil-m-38510 **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** 0.0 volts power source and 7.0 volts power source **Time Rating Per Chacteristic:** 4.50 nanoseconds propagation delay time, low to high level output and 4.50 nanoseconds propagation delay time, high to low level output **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 16 flat leads Shelf Life: N/a

## **Demilitarization:**

**Unit Of Measure:** 

Yes - demil/mli

## NSN 5962-01-168-0829

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0