## NSN 5962-01-168-3904



Linear Microcircuit - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5962-01-168-3904 **Body Length:** Between 1.430 inches and 1.470 inches **Body Width:** 0.520 inches **Body Height:** 0.200 inches **Maximum Power Dissipation Rating:** 1.2 watts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** W/enable and w/switch and hermetically sealed and burn in and w/resistor **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** 5 input and 16 channel **Design Function And Quantity:** 1 multiplexer, analog **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** 40.0 volts power source **Time Rating Per Chacteristic:** 300.00 nanoseconds propagation delay time, low to high level output and 300.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 82577-932585 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 28 printed circuit Shelf Life: N/a **Unit Of Measure:** 

Demilitarization:

Yes - demil/mli

Fiig:

A458a0