## NSN 5962-01-168-5842

Digital Microcircuit - Page 1 of 1

**Fiig:** A458a0



View Online at https://aerobasegroup.com/nsn/5962-01-168-5842 **Body Length:** 0.960 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** 0.185 inches **Maximum Power Dissipation Rating:** 715.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Bipolar and programmable and schottky and monolithic **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 12 input **Case Outline Source And Designator:** D-6 mil-m-38510 **Time Rating Per Chacteristic:** 125.00 nanoseconds propagation delay time, low to high level output and 125.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a **Unit Of Measure:** Demilitarization: Yes - demil/mli