NSN 5962-01-168-6026

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-168-6026 **Body Length:** 0.840 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** 0.185 inches **Maximum Power Dissipation Rating:** 1.025 watts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** Radar system an/fps-117 **Features Provided:** Hermetically sealed and burn in and adjustable and w/active pull-up **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** Quad 2 input **Design Function And Quantity:** 4 receiver, line **Case Outline Source And Designator:** D-2 mil-m-38510 **Terminal Surface Treatment:** Tin **Time Rating Per Chacteristic:** 44.00 nanoseconds propagation delay time, low to high level output and 40.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 03538-7849949 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a **Unit Of Measure: Demilitarization:** Yes - demil/mli

Fiig:

A458a0