NSN 5962-01-168-6031

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-168-6031
Body Length:
0.440 inches
Body Width:
Between 0.245 inches and 0.285 inches
Body Height:
Between 0.045 inches and 0.085 inches
Maximum Power Dissipation Rating:
165.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Fsas c-141/c-
Features Provided:
Hermetically sealed and burn in and 3-state output and w/enable and monolithic
Inclosure Material:
Ceramic
Inclosure Configuration:
Flat pack
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
8 input
Design Function And Quantity:
6 driver, bus
Case Outline Source And Designator:
F-5 mil-m-38510
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
5.5 volts power source
Time Rating Per Chacteristic:
17.00 nanoseconds propagation delay time, low to high level output and 16.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
35351-165089 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
16 flat leads
Shelf Life:
N/a
Unit Of Measure:

NSN 5962-01-168-6031

Digital Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0