NSN 5962-01-168-6033

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-168-6033

view Online at https://aerobasegroup.com/hsh/0302-01-100-0033
Body Length:
Between 1.030 inches and 1.090 inches
Body Width:
Between 0.620 inches and 0.660 inches
Body Height:
Between 0.070 inches and 0.115 inches
Maximum Power Dissipation Rating:
1.54 watts
Operating Tempurature Range:
55.0/+125.0 degrees celsius
Storage Tempurature Range:
65.0/+150.0 degrees celsius
End Application:
=sas c-141/c-
Features Provided:
Hermetically sealed and burn in and monolithic and bipolar and w/clock and w/enable
nclosure Material:
Ceramic
nclosure Configuration:
Flat pack
Output Logic Form:
Transistor-transistor logic
nput Circuit Pattern:
19 input
Design Function And Quantity:
1 microprocessor
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
5.5 volts power source
Time Rating Per Chacteristic:
100.00 nanoseconds propagation delay time, low to high level output and 100.00 nanoseconds propagation delay time, high to low leve
putput
Test Data Document:
35351-163540 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
42 flat leads
Shelf Life:
N/a
Unit Of Measure:

Yes - demil/mli

Demilitarization:

NSN 5962-01-168-6033

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0