## NSN 5962-01-170-1572

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-170-1572

**Body Length:** 0.840 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** 0.185 inches **Maximum Power Dissipation Rating:** 400.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Monolithic and hermetically sealed **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** Quad 1 input **Design Function And Quantity:** 4 switch, analog, single pole single throw normally open **Case Outline Source And Designator:** D-2 mil-m-38510 **Terminal Surface Treatment:** Gold **Voltage Rating And Type Per Characteristic:** 40.0 volts power source **Time Rating Per Chacteristic:** 800.00 nanoseconds propagation delay time, low to high level output and 650.00 nanoseconds propagation delay time, high to low level output **Precious Material And Location:** Terminal surfaces gold **Precious Material:** Gold

#### **Test Data Document:**

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Terminal Type And Quantity:**

16 pin

### **Specification Data:**

81349-mil-m-38510/123 government specification

Shelf Life:

NI/o

# NSN 5962-01-170-1572

Linear Microcircuit - Page 2 of 2



			ure:	

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0