## NSN 5962-01-170-1619

Linear Microcircuit - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5962-01-170-1619 |
|---|
| Body Outside Diameter:  |
| Between 0.335 inches and 0.370 inches                         |
| Body Height:  |
| Between 0.165 inches and 0.185 inches                         |
| Maximum Power Dissipation Rating:                             |
| 500.0 milliwatts  |
| Operating Tempurature Range:                                  |
| -55.0/+125.0 degrees celsius                                  |
| Storage Tempurature Range:                                    |
| -65.0/+150.0 degrees celsius                                  |
| Features Provided:  |
| Hermetically sealed and negative outputs and positive outputs |
| Inclosure Material:   |
| Metal   |
| Inclosure Configuration:                                      |
| Can   |
| Input Circuit Pattern:  |
| 2 input   |
| Design Function And Quantity:                                 |
| 1 amplifier, operational, general purpose                     |
| Terminal Surface Treatment:                                   |
| Solder  |
| Voltage Rating And Type Per Characteristic:                   |
| 22.0 volts power source                                       |
| Terminal Type And Quantity:                                   |
| 8 pin   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| Yes - demil/mli   |
| Fiig:   |
| A458a0  |