NSN 5962-01-170-6556

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-170-6556 **Body Length:** 0.440 inches **Body Width:** Between 0.245 inches and 0.285 inches **Body Height:** Between 0.045 inches and 0.085 inches **Maximum Power Dissipation Rating:** 400.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and monolithic and electrostatic sensitive and w/clock **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Flat pack **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Design Function And Quantity:** 1 shift register, static **Case Outline Source And Designator:** F-5 mil-m-38510 **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** -0.5 volts power source and 18.0 volts power source **Time Rating Per Chacteristic:** 600.00 nanoseconds propagation delay time, low to high level output and 600.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 16 flat leads Shelf Life: N/a **Unit Of Measure:**

Fiig:

A458a0

Demilitarization: Yes - demil/mli