## NSN 5962-01-171-6804

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-171-6804

View Offilite at https://defobasegroup.com/nsi//0302-01-17 1-0004
Body Length:
Between 0.710 inches and 0.760 inches
Body Width:
Between 0.275 inches and 0.300 inches
Body Height:
Between 0.060 inches and 0.120 inches
Maximum Power Dissipation Rating:
450.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Electronic warfare trainer simulator an/alq-t5
Features Provided:
Low power and monolithic
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
Dual 3 input
Design Function And Quantity:
2 switch, analog, single pole double throw
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
17.0 volts power source
Time Rating Per Chacteristic:
1000.00 nanoseconds propagation delay time, low to high level output
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
14 printed circuit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig:

A458a0