## NSN 5962-01-171-7451

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-171-7451 **Body Length:** Between 0.335 inches and 0.400 inches **Body Width:** Between 0.335 inches and 0.400 inches **Body Height:** 0.090 inches **Maximum Power Dissipation Rating:** 1225.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Bipolar and electrostatic sensitive and programmed and burn in **Inclosure Material:** Ceramic or metal **Inclosure Configuration:** Flat pack **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 12 input **Terminal Surface Treatment:** Gold **Voltage Rating And Type Per Characteristic:** 7.0 volts power source **Memory Device Type:** Rom **Precious Material And Location:** Terminal surface option gold **Precious Material:** Gold **Test Data Document:** 82577-932750 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 18 flat leads Shelf Life: N/a **Unit Of Measure:** 

Yes - demil/mli

**Demilitarization:** 

## NSN 5962-01-171-7451

Memory Microcircuit - Page 2 of 2



Fiig:

A458a0