NSN 5962-01-171-7525

Memory Microcircuit - Page 1 of 1



propagation delay time, high to low level

View Online at https://aerobasegroup.com/nsn/5962-01-171-7525

| Body Lengt | h: |
|---------------|---|
| 1.290 inches | |
| Body Width | : |
| Between 0.5 | 00 inches and 0.610 inches |
| Body Heigh | t: |
| 0.210 inches | 3 |
| Maximum P | ower Dissipation Rating: |
| 575.0 milliwa | atts |
| Operating T | empurature Range: |
| -55.0/+125.0 | degrees celsius |
| Storage Ter | npurature Range: |
| -65.0/+150.0 | degrees celsius |
| Features Pr | ovided: |
| Hermetically | sealed and monolithic and bipolar and programmable and w/open collector |
| Inclosure M | aterial: |
| Ceramic and | l glass |
| Inclosure C | onfiguration: |
| Dual-in-line | |
| Output Log | ic Form: |
| Transistor-tr | ansistor logic |
| Input Circui | t Pattern: |
| 8 input | |
| Case Outlin | e Source And Designator: |
| D-3 mil-m-38 | 3510 |
| Terminal Su | Irface Treatment: |
| Solder | |
| Voltage Rat | ing And Type Per Characteristic: |
| 5.5 volts po | wer source |
| Time Rating | Per Chacteristic: |
| 140.00 nano | seconds propagation delay time, low to high level output and 140.00 nanoseconds |
| output | |
| Memory De | vice Type: |
| Rom | |
| Terminal Ty | pe And Quantity: |
| 24 printed ci | rcuit |
| Shelf Life: | |
| N/a | |
| Unit Of Mea | sure: |
| | |
| Demilitariza | tion: |
| Yes - demil/ı | nli |
| Fiig: | |
| A458a0 | |