## NSN 5962-01-172-4202

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-172-4202 **Body Length:** 1.060 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** 0.185 inches **Maximum Power Dissipation Rating:** 2.0 watts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Bipolar and burn in and gated output and hermetically sealed and monolithic and positive outputs and programmable and w/buffered output and w/common clock and w/common enable and 3-state output and programmed **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-diode-resistor logic **Input Circuit Pattern:** 16 input **Design Function And Quantity:** 1 array, logic **Case Outline Source And Designator:** D-8 mil-m-38510 **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: -0.5 volts power source and 12.0 volts power source **Time Rating Per Chacteristic:** 25.00 nanoseconds propagation delay time, low to high level output and 25.00 nanoseconds propagation delay time, high to low level output **Terminal Type And Quantity:** 20 printed circuit Shelf Life: N/a **Unit Of Measure:** 

Fiig: A458a0

**Demilitarization:** Yes - demil/mli