Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-172-7207

Body Length:	
0.840 inches	
Body Width:	
0.310 inches	
Body Height:	
0.185 inches	
Maximum Power Dissipation Rating:	
730.0 milliwatts	
Operating Tempurature Range:	
-55.0/+125.0 degrees celsius	
Storage Tempurature Range:	
-65.0/+150.0 degrees celsius	
Features Provided:	
Hermetically sealed and burn in and w/resistor and w/strobe and adjustable	
Inclosure Material:	
Ceramic	
Inclosure Configuration:	
Dual-in-line	
Input Circuit Pattern:	
9 input	
Design Function And Quantity:	
2 receiver, line differential	
Terminal Surface Treatment:	
Solder	
Voltage Rating And Type Per Characteristic:	
15.0 volts power source	
Time Rating Per Chacteristic:	
250.00 nanoseconds propagation delay time, low to high level output and 250.00 nanoseconds propagation delay time, high to low level	
output	
Test Data Document:	
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).	
Terminal Type And Quantity:	
16 printed circuit	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
Yes - demil/mli	
Fiig:	

A458a0