## NSN 5962-01-173-6115

Linear Microcircuit - Page 1 of 1

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5962-01-173-6115

Overall Length:
0.400 inches
Overall Height:
0.080 inches
Overall Width:
0.940 inches
Body Length:
Between 0.371 inches and 0.400 inches
Body Width:
0.295 inches
Body Height:
Between 0.050 inches and 0.080 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+125.0 degrees celsius
Features Provided:
Burn in
Inclosure Material:
Ceramic
Inclosure Configuration:
Flat pack
Input Circuit Pattern:
Input Circuit Pattern: Quad 2 input
•
Quad 2 input
Quad 2 input Design Function And Quantity:
Quad 2 input Design Function And Quantity: 4 receiver, line differential
Quad 2 input Design Function And Quantity: 4 receiver, line differential Terminal Surface Treatment:
Quad 2 input Design Function And Quantity: 4 receiver, line differential Terminal Surface Treatment: Solder
Quad 2 input Design Function And Quantity: 4 receiver, line differential Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic:
Quad 2 input Design Function And Quantity: 4 receiver, line differential Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 7.0 volts power source
Quad 2 input Design Function And Quantity: 4 receiver, line differential Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 7.0 volts power source Terminal Type And Quantity:
Quad 2 input Design Function And Quantity: 4 receiver, line differential Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 7.0 volts power source Terminal Type And Quantity: 16 flat leads
Quad 2 input Design Function And Quantity: 4 receiver, line differential Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 7.0 volts power source Terminal Type And Quantity: 16 flat leads Shelf Life:
Quad 2 input Design Function And Quantity: 4 receiver, line differential Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 7.0 volts power source Terminal Type And Quantity: 16 flat leads Shelf Life: N/a
Quad 2 input Design Function And Quantity: 4 receiver, line differential Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 7.0 volts power source Terminal Type And Quantity: 16 flat leads Shelf Life: N/a Unit Of Measure:
Quad 2 input Design Function And Quantity: 4 receiver, line differential Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 7.0 volts power source Terminal Type And Quantity: 16 flat leads Shelf Life: N/a Unit Of Measure:
Quad 2 input Design Function And Quantity: 4 receiver, line differential Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 7.0 volts power source Terminal Type And Quantity: 16 flat leads Shelf Life: N/a Unit Of Measure:  Demilitarization:
Quad 2 input Design Function And Quantity: 4 receiver, line differential Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 7.0 volts power source Terminal Type And Quantity: 16 flat leads Shelf Life: N/a Unit Of Measure:  Demilitarization: No