NSN 5962-01-174-4479

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-174-4479

| Body Length: |
|---|
| Between 1.980 inches and 2.020 inches |
| Body Width: |
| Between 0.576 inches and 0.610 inches |
| Body Height: |
| Between 0.065 inches and 0.160 inches |
| Maximum Power Dissipation Rating: |
| 1.2 watts |
| Operating Tempurature Range: |
| +0.0/+70.0 degrees celsius |
| Storage Tempurature Range: |
| -55.0/+150.0 degrees celsius |
| End Application: |
| Mine countermeasures support clas (lph-12), nimitz class cvn, general purpose electronic test equipment, forrestal class cv, emory s.Land |
| class as |
| Features Provided: |
| Monolithic |
| Inclosure Material: |
| Ceramic |
| Inclosure Configuration: |
| Dual-in-line |
| Output Logic Form: |
| N-type metal oxide-semiconductor logic |
| Input Circuit Pattern: |
| 14 input |
| Design Function And Quantity: |
| 1 microprocessor |
| Terminal Surface Treatment: |
| Solder |
| Voltage Rating And Type Per Characteristic: |
| -0.3 volts power source and 7.0 volts power source |
| Special Features: |
| Frequency limit 2.0 mhz |
| Terminal Type And Quantity: |
| 40 printed circuit |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

Fiig:

A458a0

Yes - demil/mli