NSN 5962-01-175-4872

Memory Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/psn/5062-01-175-4872

| view Online at https://aerobasegroup.com/hsn/5962-01-175-4672 |
|--|
| Body Length: |
| Between 0.985 inches and 1.015 inches |
| Body Width: |
| Between 0.300 inches and 0.320 inches |
| Body Height: |
| Between 0.088 inches and 0.108 inches |
| Maximum Power Dissipation Rating: |
| 1.0 watts |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| Features Provided: |
| High performance and static operation |
| Inclosure Material: |
| Ceramic |
| Inclosure Configuration: |
| Dual-in-line |
| Output Logic Form: |
| N-type metal oxide-semiconductor logic |
| Input Circuit Pattern: |
| 17 input |
| Terminal Surface Treatment: |
| Solder |
| Voltage Rating And Type Per Characteristic: |
| 7.0 volts power source |
| Time Rating Per Chacteristic: |
| 70.00 nanoseconds propagation delay time, low to high level output |
| Memory Device Type: |
| Ram |
| Terminal Type And Quantity: |
| 20 printed circuit |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |

Fiig:

A458a0