# NSN 5962-01-176-3282

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-176-3282

## **Body Length:**

Between 0.240 inches and 0.280 inches

### **Body Width:**

Between 0.240 inches and 0.280 inches

# **Maximum Power Dissipation Rating:**

800.0 milliwatts

### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

### **Features Provided:**

Hermetically sealed and monolithic

### **Inclosure Material:**

Ceramic

### **Inclosure Configuration:**

# Flat pack

**Input Circuit Pattern:** 

Quad 2 input

## **Design Function And Quantity:**

4 amplifier, operational, linear

# **Terminal Surface Treatment:**

Solder

### Voltage Rating And Type Per Characteristic:

16.0 volts power source

### **Test Data Document:**

88818-a574a599 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,

etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

## **Terminal Type And Quantity:**

14 flat leads

Shelf Life:

N/a

### Unit Of Measure:

--

### **Demilitarization:**

Yes - demil/mli

### Fiig:

A458a0