## NSN 5962-01-176-5352

Digital Microcircuit - Page 1 of 1

A458a0



View Online at https://aerobasegroup.com/nsn/5962-01-176-5352

Body Lenght:  0.440 inches Body Width: Between 0.245 inches and 0.285 inches Body Height: Between 0.245 inches and 0.285 inches Maximum Power Dissipation Rating: 110.0 millwatts  Operating Tempurature Range: -55.0/+125.0 degrees celaius Storage Tempurature Range: -56.0/+125.0 degrees celaius Storage Tempurature Range: -65.0/+125.0 degrees celaius Features Provided: Low power and monolithic inclosure Material: Ceramic Inclosure Material: Ceramic Inclosure Material: Ceramic Inclosure Authorial: Inclosure Configuration: Flist pack Output Logic Form: Transistor-transistor logic Input Circuit Pattern: 9 input Design Function And Quantity: 1 encoder, priority, eight to three line Case Outline Source And Designator: F-6 mil-m-38510 Terminal Surface Treatment: Solider Voltage Rating And Type Per Characteristic: -05. volts power source and 7.0 volts power source Test Data Document: 14933-79027 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing. Terminal Type And Quantity: 16 flat leads Shelf Life: N/A Unit of Measure:	
Botwen 0.245 inches and 0.285 inches Body Height: Betwen 0.045 inches and 0.085 inches Maximum Power Dissipation Rating: 110.0 milliwatts Operating Tempurature Range: -55.04+125.0 degrees celsius Storage Tempurature Range: -65.04+150.0 degrees celsius Features Provided: -05.0 power and monoilithic inclosure Material: -Ceramic inclosure Material: -Ceramic inclosure Configuration: -Tiest pack Output Logic Form: -Transistor-transistor logic input Circuit Pattern: 9 input Design Function And Quantity: 1 encoder, priority, eight to three line -Case Outline Source And Designator: -Fo mil-m-38510 -Terminal Surface Treatment: Solder -Voltage Rating And Type Per Characteristic: -0.5 volts power source and 7.0 volts power source -Test Data Document: -14333-78027 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) -Terminal Type And Quantity: -16 if lat leads	Body Length:
Between 0.245 inches and 0.285 inches Body Height: Between 0.045 inches and 0.085 inches Maximum Power Dissipation Rating: 110.0 milliwatts Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provided: -65.0/+150.0 degrees celsius Features Provided: -60.0/+150.0 degrees celsius -60.0/+150.0 degree	0.440 inches
Botyle Height: Botyle no. 0.45 inches and 0.085 inches Maximum Power Dissipation Rating: 11.00 milliwatis Operating Tempurature Range: -55.04-125.0 degrees celsius Storage Tempurature Range: -55.04-125.0 degrees celsius Storage Tempurature Range: -65.04-150.0 degrees celsius Features Provided: Low power and monolithic Inclosure Material: Ceramic Inclosure Material: Ceramic Inclosure Configuration: Flat pack Output Logic Form: Transistor-transistor logic Input Circuit Pattern: 9 input Design Function And Quantity: 1 encoder, priority, eight to three line Case Outline Source And Designator: F-5 mili-m-38510 Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -0.5 volts power source and 7.0 volts power source Test Data Document: 14933-78027 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 16 fiat leads Shelf Life: Na Unit of Measure: Unit of Measure: Uniti of Measure:	Body Width:
Between 0.045 inches and 0.085 inches  Maximur Power Dissipation Rating:  1.0.0 milliwatts  Operating Tempurature Range: -55.0/+125.0 degrees celsius  Storage Tempurature Range: -65.0/+150.0 degrees celsius  Storage Tempurature Range: -65.0/+150.0 degrees celsius  Features Provided: Low power and monolithic Inclosure Material: Coramic Inclosure Configuration: Flat pack Output Logic Form: Transistor Iogic Input Circuit Pattern: 9 input  Design Function And Quantity: 1 encoder, priority, eight to three line Case Outline Source And Designator: F-5 mill-m-38510  Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -05. volts power source and 7.0 volts power source Test Data Document: 14933-78027 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 16 fiat leads Shelf Life: Na Unit of Measure: Uniti of Measure: Demilitarization:	Between 0.245 inches and 0.285 inches
Maximum Power Dissipation Rating:  110.0 milliwatts  Operating Tempurature Range: -65.0/+125.0 degrees celsius  Storage Tempurature Range: -65.0/+125.0 degrees celsius  Features Provided: Low power and monolithic Inclosure Material: Ceramic  Inclosure Material: Ceramic  Inclosure Configuration: Filat pack  Output Logic Form: Transistor-transistor logic Input Circuit Pattern: 9 input  Dosign Function And Quantity: 1 encoder, priority, eight to three line Case Outline Source And Designator: F-5 mil-m-38510  Terminal Surface Treatment: Solder  Voltage Rating And Type Per Characteristic: -0.5 volts power source and 7.0 volts power source  Test Data Document: 14933-78027 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Terminal Type And Quantity: 16 flat leads  Shelf Life: N/a  Unit Of Measure:	Body Height:
110.0 milliwatts Operating Tempurature Range: -55.04+150.0 degrees celsius Storage Tempurature Range: -65.04+150.0 degrees celsius Features Provided: -60.04+150.0 degrees Celsius -60.04+150.0 de	Between 0.045 inches and 0.085 inches
Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+125.0 degrees celsius Features Provided: Low power and monolithic Inclosure Material: Ceramic Inclosure Configuration: Flat pack Output Logic Form: Transistor-transistor logic Input Circuit Pattern: 9 input Design Function And Quantity: 1 encoder, priority, eight to three line Case Outline Source And Designator: F-5 milm-38510 Terminal Surface Treatments: 0.0ider Voltage Rating And Type Per Characteristic: -0.5 volts power source and 7.0 volts power source Test Data Document: 14933-78027 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 16 flat leads Shelf Life: N/a Unit Of Measure:	Maximum Power Dissipation Rating:
-55.0/+125.0 degrees celsius  Storage Tempurature Range: -65.0/+150.0 degrees celsius  Features Provided: Low power and monolithic Inclosure Material: Ceramic  Inclosure Configuration: Flat pack  Output Logic Form: Transistor-transistor logic Input Circuit Pattern: 9 input  Design Function And Quantity: 1 encoder, priority, eight to three line  Case Outline Source And Designator: F-5 mil-m-38510  Terminal Surface Treatment: Solder  Voltage Rating And Type Per Characteristic: -0.5 volts power source and 7.0 volts power source Test Data Document: 14933-78027 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Terminal Type And Quantity: 16 flat leads  Shelf Life: N/a  Unit Of Measure: Demilitarization:	110.0 milliwatts
Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provided: Low power and monolithic Inclosure Material: Ceramic Inclosure Configuration: Flat pack Output Logic Form: Transistor-transistor logic Input Circuit Pattern: 9 input Design Function And Quantity: 1 encoder, priority, eight to three line Case Outline Source And Designator: F5- mil-m-38510 Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -0.5 volls power source and 7.0 volls power source Test Data Document: 14933-78027 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 16 flat leads Shelf Life:  Volunt Of Measure: Demilitarization:	Operating Tempurature Range:
-65.0/+150.0 degrees celsius  Features Provided: Low power and monolithic Inclosure Material: Ceramic Inclosure Configuration: Flat pack Output Logic Form: Transistor-transistor logic Input Circuit Pattern: 9 input Design Function And Quantity: 1 encoder, priority, eight to three line Case Outline Source And Designator: F-5 mil-m-38510  Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -0.5 volts power source and 7.0 volts power source Test Data Document: 14933-78027 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 16 flat leads Shelf Life: N/a Unit Of Measure: Demilitarization:	-55.0/+125.0 degrees celsius
Features Provided: Low power and monolithic Inclosure Material: Ceramic Inclosure Configuration: Flat pack Output Logic Form: Transistor-transistor logic Input Circuit Pattern: 9 input Design Function And Quantity: 1 encoder, priority, eight to three line Case Outline Source And Designator: F-5 mil-m-38510 Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -0.5 volts power source and 7.0 volts power source Test Data Document: 14933-78027 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 16 flat leads Shelf Life: N/a Unit Of Measure: Demilitarization:	Storage Tempurature Range:
Low power and monolithic  Inclosure Material: Ceramic Inclosure Configuration: Flat pack Output Logic Form: Transistor-transistor logic Input Circuit Pattern: 9 input Orection And Quantity: 1 encoder, priority, eight to three line Case Outline Source And Designator: F-5 mil-m-38510 Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -0.5 volts power source and 7.0 volts power source Test Data Document: 14933-78027 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 16 flat leads Shelf Life: Na Unit Of Measure: Demilitarization:	-65.0/+150.0 degrees celsius
Inclosure Material: Ceramic Inclosure Configuration: Flat pack Output Logic Form: Transistor-transistor logic Input Circuit Pattern: 9 input Design Function And Quantity: 1 encoder, priority, eight to three line Case Outline Source And Designator: F-5 mil-m-38510 Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -0.5 volts power source and 7.0 volts power source Test Data Document: 14933-78027 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 16 flat leads Shelf Life: N/a Unit Of Measure: Demilitarization:	Features Provided:
Ceramic Inclosure Configuration: Flat pack Output Logic Form: Transistor-transistor logic Input Circuit Pattern: 9 input Design Function And Quantity: 1 encoder, priority, eight to three line Case Outline Source And Designator: F-5 mil-m-38510 Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -0.5 volts power source and 7.0 volts power source Test Data Document: 14933-78027 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) 16 flat leads Shelf Life: N/a Unit Of Measure: Demilitarization:	Low power and monolithic
Inclosure Configuration: Flat pack Output Logic Form: Transistor-transistor logic Input Circuit Pattern: 9 input Design Function And Quantity: 1 encoder, priority, eight to three line Case Outline Source And Designator: F-5 mil-m-38510 Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -0.5 volts power source and 7.0 volts power source Test Data Document: 14933-78027 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 16 flat leads Shelf Life: N/a Unit Of Measure: Demilitarization:	Inclosure Material:
Flat pack Output Logic Form: Transistor-transistor logic Input Circuit Pattern: 9 input Design Function And Quantity: 1 encoder, priority, eight to three line Case Outline Source And Designator: F-5 mil-m-38510 Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -0.5 volts power source and 7.0 volts power source Test Data Document: 14933-78027 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 16 flat leads Shelf Life: N/a Unit Of Measure: Demilitarization:	Ceramic
Output Logic Form:  Transistor-transistor logic Input Circuit Pattern:  9 input  Design Function And Quantity:  1 encoder, priority, eight to three line  Case Outline Source And Designator:  F-5 mil-m-38510  Terminal Surface Treatment:  Solder  Voltage Rating And Type Per Characteristic:  -0.5 volts power source and 7.0 volts power source  Test Data Document:  14933-78027 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Terminal Type And Quantity:  16 flat leads  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	Inclosure Configuration:
Transistor-transistor logic Input Circuit Pattern:  9 input Design Function And Quantity:  1 encoder, priority, eight to three line Case Outline Source And Designator: F-5 mil-m-38510 Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -0.5 volts power source and 7.0 volts power source Test Data Document: 14933-78027 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 16 flat leads Shelf Life: N/a Unit Of Measure:	Flat pack
Input Circuit Pattern:  9 input  Design Function And Quantity:  1 encoder, priority, eight to three line  Case Outline Source And Designator: F-5 mil-m-38510  Terminal Surface Treatment: Solder  Voltage Rating And Type Per Characteristic: -0.5 volts power source and 7.0 volts power source  Test Data Document: 14933-78027 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Terminal Type And Quantity: 16 flat leads  Shelf Life: N/a  Unit Of Measure: Demilitarization:	Output Logic Form:
9 input  Design Function And Quantity:  1 encoder, priority, eight to three line  Case Outline Source And Designator: F-5 mil-m-38510  Terminal Surface Treatment: Solder  Voltage Rating And Type Per Characteristic: -0.5 volts power source and 7.0 volts power source  Test Data Document: 14933-78027 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Terminal Type And Quantity: 16 flat leads Shelf Life: N/a Unit Of Measure: Demilitarization:	Transistor-transistor logic
Design Function And Quantity:  1 encoder, priority, eight to three line  Case Outline Source And Designator: F-5 mil-m-38510  Terminal Surface Treatment: Solder  Voltage Rating And Type Per Characteristic: -0.5 volts power source and 7.0 volts power source  Test Data Document: 14933-78027 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Terminal Type And Quantity: 16 flat leads  Shelf Life: N/a  Unit Of Measure: Demilitarization:	Input Circuit Pattern:
1 encoder, priority, eight to three line  Case Outline Source And Designator: F-5 mil-m-38510  Terminal Surface Treatment: Solder  Voltage Rating And Type Per Characteristic: -0.5 volts power source and 7.0 volts power source  Test Data Document: 14933-78027 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Terminal Type And Quantity: 16 flat leads  Shelf Life: N/a  Unit Of Measure: Demilitarization:	9 input
Case Outline Source And Designator: F-5 mil-m-38510  Terminal Surface Treatment: Solder  Voltage Rating And Type Per Characteristic: -0.5 volts power source and 7.0 volts power source Test Data Document: 14933-78027 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Terminal Type And Quantity: 16 flat leads Shelf Life: N/a Unit Of Measure: Demilitarization:	Design Function And Quantity:
F-5 mil-m-38510  Terminal Surface Treatment: Solder  Voltage Rating And Type Per Characteristic: -0.5 volts power source and 7.0 volts power source  Test Data Document: 14933-78027 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Terminal Type And Quantity: 16 flat leads  Shelf Life: N/a  Unit Of Measure: Demilitarization:	1 encoder, priority, eight to three line
Terminal Surface Treatment: Solder  Voltage Rating And Type Per Characteristic: -0.5 volts power source and 7.0 volts power source  Test Data Document: 14933-78027 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Terminal Type And Quantity: 16 flat leads Shelf Life: N/a Unit Of Measure: Demilitarization:	Case Outline Source And Designator:
Solder  Voltage Rating And Type Per Characteristic:  -0.5 volts power source and 7.0 volts power source  Test Data Document:  14933-78027 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Terminal Type And Quantity:  16 flat leads  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	F-5 mil-m-38510
Voltage Rating And Type Per Characteristic:  -0.5 volts power source and 7.0 volts power source  Test Data Document:  14933-78027 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Terminal Type And Quantity:  16 flat leads  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	Terminal Surface Treatment:
-0.5 volts power source and 7.0 volts power source  Test Data Document:  14933-78027 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Terminal Type And Quantity:  16 flat leads  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	Solder
Test Data Document:  14933-78027 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Terminal Type And Quantity:  16 flat leads  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	Voltage Rating And Type Per Characteristic:
14933-78027 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Terminal Type And Quantity:  16 flat leads  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	-0.5 volts power source and 7.0 volts power source
excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Terminal Type And Quantity:  16 flat leads  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	Test Data Document:
Terminal Type And Quantity:  16 flat leads  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	14933-78027 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
16 flat leads  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Shelf Life:  N/a Unit Of Measure: Demilitarization:	Terminal Type And Quantity:
N/a Unit Of Measure: Demilitarization:	16 flat leads
Unit Of Measure: Demilitarization:	Shelf Life:
Demilitarization:	N/a
	Unit Of Measure:
	<del></del>
Yes - demil/mli	Demilitarization:
	Yes - demil/mli
Fiig:	Fiig: