## NSN 5962-01-177-0593

Linear Microcircuit - Page 1 of 1



view Online at https://aerobasegroup.com/nsn/5962-01-177-0593
Body Length:
0.840 inches
Body Width:
Between 0.220 inches and 0.310 inches
Body Height:
0.185 inches
Maximum Power Dissipation Rating:
450.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Electrostatic sensitive and hermetically sealed
Inclosure Material:
Ceramic or glass or metal
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
Dual 2 channel
Design Function And Quantity:
2 switch, analog, single pole double throw
Case Outline Source And Designator:
D-2 mil-m-38510
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
36.0 volts power source
Time Rating Per Chacteristic:
200.00 nanoseconds propagation delay time, low to high level output and 125.00 nanoseconds propagation delay time, high to low leve
output
Test Data Document:
58260-13084588 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
16 printed circuit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

Fiig: A458a0

Yes - demil/mli