

View Online at <https://aerobasegroup.com/nsn/5962-01-177-1372>

Body Length:

1.290 inches

Body Width:

Between 0.500 inches and 0.610 inches

Body Height:

0.210 inches

Maximum Power Dissipation Rating:

1.4 watts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

Radar system an/fps-117

Features Provided:

Bipolar and programmable and schottky and monolithic

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

14 input

Case Outline Source And Designator:

D-3 mil-m-38510

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 7.0 volts power source

Time Rating Per Characteristic:

125.00 nanoseconds propagation delay time, low to high level output and 125.00 nanoseconds propagation delay time, high to low level output

Memory Device Type:

Rom

Test Data Document:

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

24 printed circuit

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fig:

A458a0