## NSN 5962-01-177-2450

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-177-2450

Body Length:
Between 0.735 inches and 0.750 inches
Body Width:
Between 0.243 inches and 0.261 inches
Body Height:
0.180 inches
Maximum Power Dissipation Rating:
1.0 watts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Monolithic
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
Quad 2 input
Design Function And Quantity:
4 comparator, voltage
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
36.0 volts power source
Time Rating Per Chacteristic:
300.00 nanoseconds propagation delay time, low to high level output and 300.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
14 printed circuit
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
Yes - demil/mli
Fiig:
A458a0