## NSN 5962-01-177-2469

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-177-2469

### **Body Length:** 1.480 inches **Body Width:** Between 0.500 inches and 0.610 inches **Body Height:** 0.210 inches **Maximum Power Dissipation Rating:** 1.5 watts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and bidirectional and w/enable and positive outputs and electrostatic sensitive **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 23 input **Criticality Code Justification:** Feat **Design Function And Quantity:** 1 control **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 7.0 volts power source **Time Rating Per Chacteristic:** 800.00 nanoseconds propagation delay time, low to high level output and 800.00 nanoseconds propagation delay time, high to low level output **Special Features:** Weapon system essential **Test Data Document:** 07187-8001567 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 28 printed circuit Shelf Life:

#### N/a

#### Unit Of Measure:

# NSN 5962-01-177-2469

Digital Microcircuit - Page 2 of 2

### Demilitarization:

Yes - demil/mli

Fiig:

A458a0

