NSN 5962-01-177-5398

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-177-5398 **Body Length:** Between 0.355 inches and 0.400 inches **Body Width:** Between 0.245 inches and 0.280 inches **Body Height:** 0.180 inches **Maximum Power Dissipation Rating:** 925.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** 4920-01-093-0874 velocity measur **Features Provided:** Hermetically sealed and w/common strobe and inverted output and monolithic **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** 3 input **Design Function And Quantity:** 2 driver, line **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 15.0 volts power source **Time Rating Per Chacteristic:** 60.00 nanoseconds propagation delay time, low to high level output and 45.00 nanoseconds propagation delay time, high to low level output **Terminal Type And Quantity:** 8 printed circuit Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

Yes - demil/mli

Fiig:

A458a0