NSN 5962-01-178-4143

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-178-4143

Body Length: 0.400 inches **Body Width:** Between 0.240 inches and 0.260 inches **Body Height:** 0.180 inches **Maximum Power Dissipation Rating:** 800.0 milliwatts **Operating Tempurature Range:** +0.0/+70.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and w/resistor and high voltage and high speed **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** Dual 2 input **Design Function And Quantity:** 2 driver, nand **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 5.5 volts power source **Time Rating Per Chacteristic:** 35.00 nanoseconds propagation delay time, low to high level output and 35.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 20886-252-275452 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 8 printed circuit Shelf Life: N/a Unit Of Measure: **Demilitarization:** Yes - demil/mli Fiig: A458a0