# NSN 5962-01-178-9205

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-178-9205

# **Body Length:**

0.840 inches

# **Body Width:**

Between 0.220 inches and 0.310 inches

# **Body Height:**

0.185 inches

## **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

# **Features Provided:**

Monolithic

## **Inclosure Material:**

Ceramic

#### Inclosure Configuration:

Dual-in-line

# Input Circuit Pattern:

Quad 2 input

# **Design Function And Quantity:**

4 switch, analog, single pole single throw normally open

## **Case Outline Source And Designator:**

D-2 mil-m-38510

# **Terminal Surface Treatment:**

Solder

## Voltage Rating And Type Per Characteristic:

40.0 volts total supply

## **Time Rating Per Chacteristic:**

800.00 nanoseconds propagation delay time, low to high level output and 650.00 nanoseconds propagation delay time, high to low level output

## **Test Data Document:**

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Terminal Type And Quantity:**

16 printed circuit

#### **Specification Data:**

81349-mil-m-38510/123 government specification

#### Shelf Life:

N/a

# Unit Of Measure:

---

#### Demilitarization:

Yes - demil/mli

# Fiig: