NSN 5962-01-179-3628

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-179-3628 **Body Length:** 1.290 inches **Body Width:** Between 0.500 inches and 0.610 inches **Body Height:** 0.210 inches **Maximum Power Dissipation Rating:** 635.0 milliwatts **Operating Tempurature Range:** -55.0/+100.0 degrees celsius Storage Tempurature Range: -65.0/+125.0 degrees celsius **Features Provided:** Programmable and ultraviolet erasable and monolithic **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** N-type metal oxide-semiconductor logic **Input Circuit Pattern:** 13 input **Case Outline Source And Designator:** D-3 mil-m-38510 **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** 5.5 volts power source **Time Rating Per Chacteristic:** 450.00 nanoseconds propagation delay time, low to high level output **Memory Device Type:** Rom **Test Data Document:** 14933-78022 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 24 printed circuit Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

Yes - demil/mli

NSN 5962-01-179-3628

Memory Microcircuit - Page 2 of 2



Fiig:

A458a0