NSN 5962-01-179-4884

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-179-4884

Body Length:
Between 1.380 inches and 1.420 inches
Body Width:
Between 0.568 inches and 0.600 inches
Body Height:
Between 0.080 inches and 0.140 inches
Maximum Power Dissipation Rating:
1200.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and w/enable
Inclosure Material:
Ceramic and metal
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
Figure and 40 abandal
5 input and 16 channel
Design Function And Quantity:
Design Function And Quantity:
Design Function And Quantity: 1 switch, analog
Design Function And Quantity: 1 switch, analog Terminal Surface Treatment:
Design Function And Quantity: 1 switch, analog Terminal Surface Treatment: Solder
Design Function And Quantity: 1 switch, analog Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic:
Design Function And Quantity: 1 switch, analog Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 16.0 volts power source
Design Function And Quantity: 1 switch, analog Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 16.0 volts power source Test Data Document:
Design Function And Quantity: 1 switch, analog Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 16.0 volts power source Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Design Function And Quantity: 1 switch, analog Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 16.0 volts power source Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity:
Design Function And Quantity: 1 switch, analog Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 16.0 volts power source Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 28 printed circuit
Design Function And Quantity: 1 switch, analog Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 16.0 volts power source Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 28 printed circuit Shelf Life:
Design Function And Quantity: 1 switch, analog Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 16.0 volts power source Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 28 printed circuit Shelf Life: N/a
Design Function And Quantity: 1 switch, analog Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 16.0 volts power source Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 28 printed circuit Shelf Life: N/a
Design Function And Quantity: 1 switch, analog Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 16.0 volts power source Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 28 printed circuit Shelf Life: N/a Unit Of Measure:

A458a0