## NSN 5962-01-179-6959

Digital Microcircuit - Page 1 of 1

A458a0



View Online at https://aerobasegroup.com/nsn/5962-01-179-6959

view Offilite at https://defobasegroup.com/hsh/0302-01-173-0303
Body Length:
Between 1.200 inches and 1.300 inches
Body Width:
Between 0.500 inches and 0.600 inches
Body Height:
0.320 inches
Maximum Power Dissipation Rating:
1.5 watts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Circuit card assembly
Features Provided:
Monolithic and hermetically sealed and negative outputs and positive outputs and high speed and 3-state output and programmable and
w/decoded output and w/buffered output
Inclosure Material:
Ceramic and metal
Inclosure Configuration:
Dual-in-line
Output Logic Form:
N-type metal oxide-semiconductor logic
Input Circuit Pattern:
10 input
Time Rating Per Chacteristic:
20.00 nanoseconds propagation delay time, low to high level output and 20.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
Yes - demil/mli
Fiig: