NSN 5962-01-179-7216

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-179-7216
Body Length:
Between 0.740 inches and 0.870 inches
Body Width:
Between 0.220 inches and 0.310 inches
Body Height:
0.185 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and electrostatic sensitive and low power
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Input Circuit Pattern:
10 input
Design Function And Quantity:
4 multiplexer/demultiplexer, analog
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
18.5 volts power source
Time Rating Per Chacteristic:
90.00 nanoseconds propagation delay time, low to high level output and 90.00 nanoseconds propagation delay time, high to low level output
Test Data Document:
06424-2610535 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
16 printed circuit
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
Yes - demil/mli

Fiig:

A458a0